

# mDNS Services

Skaarhoj panel use mDNS to announce themselves on the network to make panel discovery easy for users. There are some network structures that can make it desired for this to be disabled.

To disable this service add **disablemdns** into the log string in the System Manager package on the packages page.

The screenshot shows the Skaarhoj System Manager interface. The top navigation bar includes 'System', 'Home', 'Configuration', 'Simulator', 'Packages', and 'Settings'. The 'Device' is identified as 'Heather's BP'. The main content area displays the 'Package > system-manager, Version: 1.0.8' page. On the left, there's a status section with a green 'Running' indicator, a 'Restart' button, and an 'Auto Start' toggle. On the right, there are 'Download Logs' and 'Backup Data' buttons. The central log window shows a series of system messages, including warnings about wpa\_supplicant, wpa\_cli, hostapd, and dnsmasq processes already being gone. A red arrow labeled 'Confirm' points to the 'Confirm' button. Below the log, there's a 'Select Log Level' dropdown set to 'Empty'. A red box highlights the 'disablemdns' command in the log string input field, with a 'Save' button next to it. A red text label 'Enter command and save' is positioned below the input field.

Revision #1

Created 17 June 2025 11:55:27 by Heather Pedersen

Updated 17 June 2025 12:18:46 by Heather Pedersen